



Housing Material	Plastic
Housing Color	White
Housing Surface	Matt
Material of Lens	Plastic
Surface Structure of Lens	Opal
Protection Class	Protection class II/protective insulation
Rated Input	8 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	No
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	50000
Power Consumption	8 kWh/1000h
Energy Efficiency Class	F

Light Source	LED, Light source not changeable
Color Temperature	3000/4000/6000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	760 lm
Luminous Efficiency	95 lm/W
Rated Angle of Reflection	90 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	58 mm
Diameter	113 mm
Installation Depth	55 mm
Cut Out Diameter	90 mm
Product weight	150 g

