



Product Features

LC-D/SC-D patch cord, OS2 yellow, 5m
- MM-fibre, G50/125 Åm, grade C3 or SM-Faser E9/125Åm, grade C1
- low insertion loss
- latch for connector locking at LC
- Push-Pull - connector locking at SC
- pre-polished ceramic ferrule, 1,25 mm(LC) / 2,5mm(SC)
- with kink protection sleeves
- life > 1000 cycles
- 5 m

Features

General	
Design	plug, ceramic sleeve
Classification	OS2
Halogen Free	Yes
Country of manufacture	CN
GTIN (EAN)	4043921665121
Dimensions/Weights without packaging	
Cable length mm	5.000
Cable diameter mm	3
Cable construction	9/125µm, Grade C1
Net weight piece kg	0,038
Certifications	
RoHS conform	Yes
Logistics Information	
Packaging	polybag
Packaging unit Quantity	1
Packaging unit Weight kg	0,044
Packaging unit Width mm	180
Packaging unit Height mm	210
Packaging unit Depth mm	20
References	
Accessories	228030006, 228030012, 228030024, 228030106, 228030112, 228030124, 228030206, 228030212, 228030224, 228030306, 228030312, 228030324, 228030506, 228030512, 228030524, 228030606, 228030612, 228030624, 228030706, 228030712, 228030724, 228030806, 228030812, 228030824
Similar article	228050305, 228050805, 228050905, 228051005, 228051105,

LC-D/SC-D Patchkabel OS2 gelb 5m

Article no.: 228051205

Color: yellow (ähnlich RAL-Nr. 1016)



228051202, 228051605