



#### Special features

- Base L x W x H: 65 x 40 x 60 mm
- Including 10 m connecting cable with WEIPU IP67 plug

<b>Housing Material</b>	Stainless steel
<b>Housing Color</b>	Silver
<b>Material of Lens</b>	Acryl
<b>Protection Class</b>	Protection class III/safety extra-low voltage
<b>Operating Mode</b>	Constant voltage
<b>Rated Input</b>	10 W
<b>Rated Input Voltage</b>	24 V/DC
<b>Power Supply Unit incl.</b>	No
<b>Connection Cable Secondary</b>	Yes
<b>Secondary Connection</b>	WEIPU plug 2-pole
<b>Secondary Cable Length</b>	10 m
<b>Dimmable</b>	Yes
<b>Control technology</b>	Dimmable via optional controller
<b>Motion Detector</b>	No

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	670 lm
<b>Rated Angle of Reflection</b>	25 Degree
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic 120°</b>	DLS

<b>Swivel Angle</b>	180 Degree
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Top

<b>Length</b>	95 mm
<b>Width</b>	106 mm
<b>Height</b>	150 mm
<b>Diameter</b>	95 mm

<b>Base length</b>	65 mm
<b>Base width</b>	40 mm
<b>Base height</b>	60 mm
<b>Working Temperature</b>	-20 to 50 °C
<b>Storage Temperature</b>	-20 to 60 °C
<b>IP Protection Class</b>	IP 68/max. 2 m
<b>IK Protection Class</b>	IK10
<b>Energy Efficiency Class</b>	G
<b>Power Consumption</b>	10 kWh/1000h
<b>Life Time L70 / B50</b>	25000 h
<b>Switching Cycles</b>	100000