

Connector - with screwless terminals, for harsh applications



Product description	
BALS-Prd.-Nr	31299
EAN	4024941312998
Product category	Connector QUICK-CONNECT TE
Current	16A
Number of poles	3p
Arrangement of phases	2P+PE
Position of earth contact	9 h
Voltage	380 - 415V~

Product description	
Frequency	50/60Hz
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure red RAL 3000, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035
Connection design	screwless spring terminals as cage clamp with Kontex-contact
Maximum conductor size	2,5 qmm
Cable entry	Cable gland
Height	163mm
Width	71mm
Depth	77mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	For cable diameter from 8 up to max. 18 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings

Logistics data	
Weight/pcs	0.174 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941312998
Length	77 mm
Width	71 mm
Height	163 mm
Weight	0.175 kg
Volume	891.121 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941823517
Length	245 mm
Width	177 mm
Height	185 mm
Weight	1.873 kg
Volume	7,140 ccm

