

Plug - with screwless terminals, for harsh applications



| Product description | |
|---------------------------|-----------------------|
| BALS-Prd.-Nr | 210171 |
| EAN | 4024941100106 |
| Product category | QUICK-CONNECT TE plug |
| Current | 16A |
| Number of poles | 3p |
| Poles | 2P+PE |
| Position of earth contact | 2 h |
| Voltage | > 50V |
| Frequency | over 300 up to 500Hz |

| Product description | |
|------------------------|--|
| Protection degree | IP44 |
| Colour code | green RAL 6002 |
| Colour of appliance | Cable gland grey RAL 7035, Housing cover green RAL 6002, Collar green RAL 6002 |
| Connection design | screwless spring-clamp technology |
| Maximum conductor size | 2,5 qmm |
| Cable entry | Cable gland |
| Height | 147mm |
| Width | 51mm |
| Depth | 59mm |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties | |
|---------------------------------|---|
| | For cable diameter from 8 up to max. 18 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.126 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941100106 |

| Logistics data | |
|----------------|---------------|
| Length | 59 mm |
| Width | 51 mm |
| Height | 147 mm |
| Weight | 0.127 kg |
| Volume | 442.323 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941831741 |
| Length | 248 mm |
| Width | 158 mm |
| Height | 123 mm |
| Weight | 1.357 kg |
| Volume | 3,960 ccm |

