



Special features

- Including 0.5 m connecting cable with WEIPU plug

Housing Material	Stainless steel, Die-cast aluminium
Housing Color	Silver
Material of Lens	Glass
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	0.6 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	WEIPU plug 2-pole
Secondary Cable Length	0.5 m
Dimmable	Yes
Control technology	Dimmable via optional controller
Motion Detector	No

Cut Out Diameter	42 mm
Product weight	230 g
Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Load Force max.	5 kN
Life Time L70 / B50	25000 h
Switching Cycles	100000
Power Consumption	1 kWh/1000h

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	14 lm
Luminous Efficiency	23.3 lm/W
Rated Angle of Reflection	120 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Length	45 mm
Width	45 mm
Height	65 mm
Installation Depth	83 mm