



Housing Material	Stainless steel, Die-cast aluminium
Housing Color	Silver
Housing Surface	Granite look
Material of Lens	Glass
Surface Structure of Lens	Transparent

Protection Class	Protection class III/safety extra-low voltage
-------------------------	---

Operating Mode	Constant voltage
Rated Input	16.9 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	WEIPU plug 4-pole
Secondary Cable Length	0.5 m
Dimmable	Yes
Control technology	Dimmable via optional controller
Motion Detector	No

Light Source	LED, Light source not changeable
Colour Consistency	6 SDCM
Rated Luminous Flux	510 lm
Luminous Efficiency	30.2 lm/W
Rated Angle of Reflection	50 Degree
Rated Angle of Reflection 2	35 Degree
Light Distribution	Asymmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Height	111 mm
Diameter	173 mm
Installation Depth	153 mm

Cut Out Diameter	157 mm
Product weight	1750 g

Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Load Force max.	20 kN

Life Time L70 / B50	25000 h
Switching Cycles	15000
Power Consumption	17 kWh/1000h