

Wall mounting socket outlet, fused - housing dimensions 260x160, with fuse base D 02



| Product description | |
|-------------------------------|---------------------------------------|
| BALS-Prd.-Nr | 15081 |
| EAN | 4024941150811 |
| product category (PG) | TE wall mounting socket outlet, fused |
| current (A) | 63A |
| number of poles (P99) | 4p |
| number of poles (P) | 3P+PE |
| position of earth contact (H) | 6 h |
| voltage (V) | 380 up to 415V |

| Product description | |
|-----------------------------|--|
| frequency (HZ) | 50 and 60Hz |
| protection degree (SA) | IP44 |
| colour code 1 (KF1) | red RAL 3000 |
| Colour of appliance | Operating window smoky topaz, Hinged lid red RAL 3000, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035 |
| connection design (AT) | screw terminal as box terminal with Kontex-contact |
| maximum conductor size (LQ) | 25.0 qmm |
| cable entry (KE) | top entry M40 bottom entry M40/M32 |
| Height | 303mm |
| Width | 160mm |
| Depth | 185mm |
| dimension of enclosure (GG) | 260x160 mm (HxW) |
| material of enclosure (GM) | Polycarbonate |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties | |
|---------------------------------|--|
| | The cable entry is one at top and two at bottom open |
| | With fuse base 3 pole D02 |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 2.144 kg / Piece |

| Logistics data | |
|----------------|---------------|
| Packaging | Carton |
| Content amount | 1 ST |
| EAN | 4024941150811 |
| Length | 325 mm |
| Width | 217 mm |
| Height | 210 mm |
| Weight | 2.36 kg |
| Volume | 13,588.4 ccm |



14 MB 14