

Artikel Nr.: 000097

Netzgerät (CV, AC) dimmbar, ABN Transformator, DIM, CV, 11,5V AC, 20 W, IP20



IP 20 CE

Elektrische Daten

Betriebsart	Spannungskonstant	Eingangsspannung	220-240 V/AC 50 / 60 Hz
Leistung	11,5-20,0 W	Leistungsfaktor	
Ausgangsspannung	11,5 V/AC	Anschlußmöglichkeit	
Ausgangsstrom	1000-1660 mA		

Produkteigenschaften

 Schutzklasse II	 Überspannungsschutz
SELV Schutzkleinspannung	 Lampenbetriebsgerät 110
 Kurzschlußfest	 Möbeleinbau nicht geeignet
 Überlastschutz	ErP Standby-Stromverbrauch < 0,5 W
 Übertemperaturschutz	LVD Sicherheit nach EN 61347
 Sicherheitstrafo	EMC Funkentstörung + Störfestigkeit nach EN 55015 + EN 61547
 dimmbar - Phasenanschnittsdimmer	EMC Netzstromoberwellen + Flicker nach EN 61000-3-2 + EN 61000-3-3

Schwarze Felder sind zutreffend / graue Felder sind nicht zutreffend

Artikel Nr.: 000097

Netzgerät (CV, AC) dimmbar, ABN Transformator, DIM, CV, 11,5V AC, 20 W, IP20

Abmessungen und Gewicht

Grenzwerte

Länge	82,00 mm	Betriebstemperatur	
Breite	56,00 mm	Gehäusetemperatur	
Höhe	50,00 mm	max. Menge Sicherungsautomaten	
Durchmesser	0,00 mm	max. Einschaltstrom	
Gewicht	1373 g	kapazitive Last	

Article No.: 000097

Power supply unit (CV, AC) dimmable, ABN transformer, DIM, CV, 11.5 V AC, 20 W, IP20













IP 20 CE

Electrical Characteristics

Operating mode	Constant voltage	Input voltage	220-240 V/AC 50 / 60 Hz
Power	11,5-20,0 W	Power factor	
Output voltage	11,5 V/AC	Connection possibility	
Output current	1000-1660 mA		

Product features

 Protection class II	 Overvoltage protection
 Low voltage protection	 Lamp control gear 110
 Short circuit protection	 Not suitable for furniture installation
 Overload protection	ErP Standby-power consumption < 0,5 W
 Overheating protection	LVD Safety according to EN 61347
 Safety transformer	EMC Interference suppression + immunity according to EN 55015 + EN 61547
 dimmable - Leading-edge dimmer	EMC Mains harmonics + flicker according to EN 61000-3-2 + EN 61000-3-3

Black fields are applicable / gray fields are not applicable

Article No.: 000097

Power supply unit (CV, AC) dimmable, ABN transformer, DIM, CV, 11.5 V AC, 20 W, IP20

Dimensions & Weight**Absolute maximum ratings**

Length	82,00 mm	Operating temperature	
Width	56,00 mm	Case temperature	
Height	50,00 mm	max. amount of circuit breakers	
Diameter	0,00 mm	max. inrush current	
Product weight	1373 g	capacitive load	