



The new COLT series is a genuine all-rounder outdoors: Powerful, freely rotatable and tiltable and equipped with the latest LED technology, the surface-mounted lamps deliver atmospheric illumination concepts in any outdoor application and cut a fine figure even when switched off thanks to their striking design.

Special features

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

Housing Material	Die-cast aluminium
Housing Color	Black
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	65 W
Rated Input Voltage Frequency	180-264 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	No
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	5260 lm
Rated Angle of Reflection	15 Degree
Light Distribution	Asymetric
Distribution Characteristic 120°	DLS

Swivel Angle	90 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Length	162 mm
Height	192 mm
Diameter	182 mm
Base height	65 mm
Base diameter	160 mm

Working Temperature	-20 to 40 °C
Storage Temperature	-30 to 60 °C

IP Protection Class	IP 65
Life Time L70 / B50	50000 h
Switching Cycles	25000
Power Consumption	65 kWh/1000h
Energy Efficiency Class	G