



Housing Material	Die-cast aluminium	Life Time L80 / B20	50000 h
Housing Color	Black	Switching Cycles	50000
Housing Surface	Powder-coated	Power Consumption	160 kWh/1000h
Material of Lens	Polycarbonate - PC	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class C.
Protection Class	Protection class I/protective grounding		
Operating Mode	Constant current		
Rated Input	160 W		
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Open cables		
Primary Cable Length	1.5 m		
Dimmable	Yes		
Control technology	DALI 2 / DT6		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	5700 K		
Colour Consistency	5 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	28800 lm		
Rated Angle of Reflection	120 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	122 mm		
Diameter	400 mm		
Working Temperature	-20 to 50 °C		
Storage Temperature	-20 to 60 °C		
IP Protection Class	IP 65		
IK Protection Class	IK09		