

## Panel mounting socket outlet, angled - flange 100x92, fixing centers 85x77



| Product description           |  |
|-------------------------------|--|
| BALS-Prd.-Nr                  | 12848  |
| EAN                           | 4024941128483                                      |
| product category (PG)         | Panel mounting socket outlet Quick-Connect, angled |
| current (A)                   | 32A  |
| number of poles (P99)         | 4p   |
| number of poles (P)           | 3P+PE  |
| position of earth contact (H) | 6 h  |
| voltage (V)                   | 380 up to 415V                                     |

| Product description            |  |
|--------------------------------|--|
| frequency (HZ)                 | 50 and 60Hz  |
| protection degree (SA)         | IP67   |
| colour code 1 (KF1)            | red RAL 3000   |
| Colour of appliance            | Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035 |
| connection design (AT)         | screwless spring terminals as cage clamp with Kontex-contact                 |
| maximum conductor size (LQ)    | 10,0 qmm   |
| cable entry (KE)               | other  |
| Height                         | 110mm  |
| Width                          | 94mm   |
| Depth                          | 122mm  |
| Flange size vertical           | 100mm  |
| Flange size horizontal         | 92mm   |
| Drill hole distance vertical   | 85mm   |
| Drill hole distance horizontal | 77mm   |
| material of enclosure (GM)     | Polyamide  |
| contact                        | The contact carrier is made of polyamide, The contacts are brass             |

| Additional technical properties |                        |
|---------------------------------|------------------------|
|                                 | The inclination is 20° |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.265 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |
| EAN            | 4024941128483    |
| Length         | 122 mm           |
| Width          | 94 mm            |
| Height         | 110 mm           |
| Weight         | 0.266 kg         |
| Volume         | 1,261.48 ccm     |
| Packaging      | Carton           |
| Content amount | 10 ST            |
| EAN            | 4024941830614    |
| Length         | 122 mm           |
| Width          | 222 mm           |
| Height         | 538 mm           |
| Weight         | 2.988 kg         |
| Volume         | 14,332.32 ccm    |



4 MB 115

| Ampere                     | 16   | 16    | 16    | 32    | 32    | 32    |
|----------------------------|------|-------|-------|-------|-------|-------|
| Polzahl                    | 3    | 4     | 5     | 3     | 4     | 5     |
| a                          | 74,0 | 100,0 | 100,0 | 100,0 | 100,0 | 100,0 |
| b                          | 62,0 | 92,0  | 92,0  | 92,0  | 92,0  | 92,0  |
| c                          | 60,0 | 85,0  | 85,0  | 85,0  | 85,0  | 85,0  |
| d                          | 52,0 | 77,0  | 77,0  | 77,0  | 77,0  | 77,0  |
| e ø                        | 5,5  | 5,5   | 5,5   | 5,5   | 5,5   | 5,5   |
| f                          | 8,0  | 8,0   | 8,0   | 8,0   | 8,0   | 8,0   |
| h                          | 46,0 | 46,0  | 46,0  | 55,0  | 55,0  | 55,0  |
| i                          | 57,0 | 57,0  | 60,0  | 65,0  | 65,0  | 69,0  |
| k                          | 57,0 | 65,0  | 70,0  | 75,0  | 75,0  | 78,0  |
| l                          | 52,0 | 65,0  | 70,0  | 75,0  | 75,0  | 78,0  |
| α                          | 20°  | 20°   | 20°   | 20°   | 20°   | 20°   |
| Leiter mm <sup>2</sup> min | 1,5  | 1,5   | 1,5   | 2,5   | 2,5   | 2,5   |
| Leiter mm <sup>2</sup> max | 4    | 4     | 4     | 10    | 10    | 10    |