



Special features

- Suitable for workplaces with screens
- Light colour adjustable in 3 stages
- 230 V direct connection
- Including power supply
- Low housing depth

Housing Material	Aluminium
Housing Color	White
Protection Class	Protection class II/protective insulation
Rated Input	40 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

IK Protection Class	IK08
Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	40 kWh/1000h
Energy Efficiency Class	F

Light Source	LED, Light source not changeable
Color Temperature	3000/4000/5700 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	3300 lm
Luminous Efficiency	82.5 lm/W
Rated Angle of Reflection	100 Degree
UGR	19
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	620 mm
Width	620 mm
Height	10 mm
Product weight	3240 g

Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 40 °C
IP Protection Class	IP 20