



The UNI II series includes high-quality surface-mounted lamps for use on walls and ceilings in commercial and private spaces. The rotatable and swivelling lamp heads have warm white COB LEDs and if required can be folded flush to the mount to shine vertically downwards like a ceiling spotlight. In addition to the single, double and triple designs, there is both a mini version (with smaller lamp head and mount) and a MAX version available. There is also a variant for use in current tracks.

**Special features**

- High colour rendering
- Can be rotated and swivelled
- Dimmable

<b>Housing Material</b>	Die-cast aluminium, Steel, Polycarbonate	<b>IP Protection Class</b>	IP 20
<b>Housing Color</b>	Black	<b>Life Time L70 / B50</b>	50000 h
<b>Material of Lens</b>	Polycarbonate - PC	<b>Life Time L80 / B10</b>	50000 h
<b>Protection Class</b>	Protection class I/protective grounding	<b>Switching Cycles</b>	50000
<b>Rated Input</b>	21 W	<b>Power Consumption</b>	21 kWh/1000h
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class F.
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	2700 K		
<b>Colour Consistency</b>	3 SDCM		
<b>Colour Rendering Index (Ra)</b>	90		
<b>Rated Luminous Flux</b>	1240 lm		
<b>Rated Angle of Reflection</b>	36 Degree		
<b>Swivel Angle</b>	90 Degree		
<b>Rotation Angle</b>	350 Degree		
<b>Light Exit Surfaces</b>	2		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Length</b>	160 mm		
<b>Width</b>	75 mm		
<b>Height</b>	91 mm		
<b>Working Temperature</b>	-10 to 55 °C		
<b>Storage Temperature</b>	-20 to 60 °C		