



**Special features**

- Robust housing
- Flicker-free
- Short-circuit-proof, overload protection, overheating protection
- Compact design

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Grey
<b>Operating Mode</b>	Constant voltage
<b>Protection Class</b>	Protection class I/protective grounding
<b>Power</b>	40 W
<b>Output Voltage</b>	24 V/DC
<b>Output Current</b>	0-1670 mA
<b>Power Factor</b>	0.96
<b>Connection Type</b>	Open cables
<b>Primary Connection</b>	With free strand / conductor ends
<b>Secondary Connection</b>	Open cables
<b>Number of Circuit Breaker B10A max.</b>	5
<b>Number of Circuit Breaker B16A max.</b>	9
<b>Number of Circuit Breaker C10A max.</b>	12
<b>Number of Circuit Breaker C16A max.</b>	19
<b>Inrush Current max.</b>	30 A / 300 µs
<b>Capacitive Load</b>	626.3 nF
<b>Reference Point Tc</b>	80 °C
<b>Working Temperature</b>	-20 to 50 °C
<b>Storage Temperature</b>	-20 to 70 °C
<b>IP Protection Class</b>	IP 67
<b>Life Time</b>	50000 h
<b>Length</b>	176 mm
<b>Width</b>	58 mm
<b>Height</b>	30.5 mm
<b>Product weight</b>	560 g

