

## har-SAB M12/4/4p PAC 10m PUR



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                 |
|--------------------|---------------------------------------------------------------------------------|
| Part number        | 09 07 001 0120 0                                                                |
| Specification      | har-SAB M12/4/4p PAC 10m PUR                                                    |
| HARTING eCatalogue | <a href="https://harting.com/090700101200">https://harting.com/090700101200</a> |

### Identification

|               |                                                     |
|---------------|-----------------------------------------------------|
| Series        | Circular connectors M12                             |
| Element       | Distribution boxes                                  |
| Specification | Pre-assembled master cable<br>With LED green/yellow |

### Version

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| Cable length          | 10 m                                              |
| Core structure        | 3x 0.75 mm <sup>2</sup> + 4x 0.34 mm <sup>2</sup> |
| Total number of ports | 4                                                 |
| Number of contacts    | 4                                                 |

### Technical characteristics

|                                        |                    |
|----------------------------------------|--------------------|
| Rated current                          | 9 A                |
| Rated voltage                          | 10 V DC<br>30 V DC |
| Limiting temperature                   | -30 ... +85 °C     |
| Degree of protection acc. to IEC 60529 | IP67               |
| Number of channels per port            | 1                  |
| Circuit logic                          | PNP                |

### Material properties

|                  |                    |
|------------------|--------------------|
| Material (cable) | PUR (polyurethane) |
| RoHS             | compliant          |
| ELV status       | compliant          |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |               |
|--------------------------------------|---------------|
| China RoHS                           | e             |
| REACH Annex XVII substances          | Not contained |
| REACH ANNEX XIV substances           | Not contained |
| REACH SVHC substances                | Not contained |
| California Proposition 65 substances | Yes           |
| California Proposition 65 substances | Nickel        |

## Specifications and approvals

|          |                         |
|----------|-------------------------|
| UL / CSA | UL 2238 CYJV.E500416    |
|          | CSA-C22.2 CYJV7.E500416 |

## Commercial data

|                                |                                                         |
|--------------------------------|---------------------------------------------------------|
| Packaging size                 | 1                                                       |
| Net weight                     | 1 g                                                     |
| Country of origin              | China                                                   |
| European customs tariff number | 85371098                                                |
| GTIN                           | 5713140276956                                           |
| eCl@ss                         | 27440108 Passive Sensor-Actuator-Interface (with cable) |
| ETIM                           | EC002585                                                |
| UNSPSC 24.0                    | 31251501                                                |