BATTERY TRANSPORTION INFORMATION

| | | , as applicable: | Cell, battery or product manufacturer's contact information to | | | |
|--|---------------|---|--|---|---|---|
| Item Number . 1834297 | | | # 1 / 10 / Company State State State State (1900) 10 / 10 / 10 / 10 / 10 / 10 / 10 / 1 | include address, phone number, email address and website for | | |
| Item Name : RS PRO CR1225 Button Battery, 3V Item Description : RS PRO CR1225 Button Battery, 3V, 12.5mm Diameter | | more information: RS Components Ltd Birchington Road Corby Northants NN17 9RS United Kingdom Tel: +44 (0) 845 850 9900 RSWWW.COM Email: RCustomer Services UK@rs-components.com | | | | |
| Name of the test laboratory to i | achule addese | e nhona numbar | A unique test report id | | Date of the test report: | _ |
| Name of the test laboratory to include address, phone number, email address and website for more information: | | | number: | CHUICAUOT | Date of the test report. | |
| Guangzhou Customs District Technology Centre Room C102, | | | 01051900007748- | 01051900007748-1(E) | | |
| Nanxiangzhi Road, | | | List of tests conducted | f and results (i.e. | pass/fail): | |
| Science City, | | | Dan or table consistent | and results (i.e. | , | |
| Guangzhou, Guangdong, China | | | Test T.1: Attitude Simulation Test T.2: Thermal Test | | Pass | |
| | | | | | Pass | |
| | | | Test T 3: Vibration | Test T.3: Vibration Test T.4: Shock | | |
| Email: itl@itqc.cn www.iqtc.cn Tet:+86-020-38669019 | | | | | | |
| Description of cell or battery to include at a minimum: Lithium ion or | | | | | Pass Pass | |
| Lithium metal cell or battery; Mass; Watt-hour rating, or lithium | | | 100 may 100 to 100 to 100 miles | Test T.5: External short circuit | | |
| content; Physical description of the cell/battery; and Model numbers: | | Test T.6 Impact/Crush | | Pass | | |
| | | | Test T.7: Overcharg | ge e | : N/A | |
| | | | Test T.8: Forced dis | charge | Pass | |
| | | | * | - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 - 1000 | | |
| Cell/battery Type | ithium Met | al | Testing additional co | mments: | | |
| Cell or Battery Cell | | | | | | |
| | | | | | | |
| LC or W/h rating 0.013g | | | | | | |
| Cell or Battery Weight | .9g | | | | | |
| Reference to assembled battery testing Reference to the revised ex | | CONTRACTOR OF THE PARTY OF THE | | | | |
| requirements, if applicable (i.e., 38 3.3(f) of Tests and Criteria used and 38.3.3;(g)): amendments thereto, if am | | | State of Charge? /SG/AC.10/11Rev.6/ | | | |
| UN Manual Of Tests ST | | | | | | |
| N/A | | Amend.1 Section38.3 | | N/A | | |
| | PRODUC | T CLASSIFICATION FOR | TRANSPORT (According | g to UN - DGP |) | |
| UN Classification: | Pro | per Shipping Name: | | | | |
| 3090 | ~ Li | thium Metal Batteries v | | | | |
| validity of information provided: Andrew Shorley RS Pro Engineering Manager | | | This document remains valid as long as no changes, modifications, or additions are made to the model(s) described in this document, after being transported from a Manufacturer XYZ facility. The model(s) has (have) been classified according to the applicable transport regulations and the UN Manual of Tests and Criteria as of the | | | |
| Date document was generated: | | | date of the certification. The model(s) must be packaged, labeled, and documented according to country and other international regulations for transportation. | | | |