

**Special features**

- integrated power supply unit for 230V direct connection
- through-wiring possible
- dimmable via leading edge/trailing edge phase
- suitable for 68 mm switch boxes of normal and deep design

Housing Material	Aluminium, Polycarbonate
Housing Color	White
Protection Class	Protection class I/protective grounding
Rated Input	4 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Number of Cable Entries	3 PCS
Dimmable	Yes
Control	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No
Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	3 SDCM
Colour consistency light source	3 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	630 lm
Luminous Efficiency	129 lm/W
UGR	19
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Front
Height	41 mm
Diameter	71.5 mm
Installation Depth	39 mm
Required Installation Depth	60 mm
Cut Out Diameter	68 mm
Product weight	90 g

Working Temperature	-20 to 40 °C
Storage Temperature	-40 to 80 °C
IP Protection Class	IP 20
IK Protection Class	IK05
Life Time L70 / B50	132000 h
Life Time L80 / B50	84000 h
Switching Cycles	50000
Power Consumption EEI	4 kWh/1000h E