




LED recessed spot set, phase dimmable

**Artikel-Nr. 39141023**



LED recessed spot set, phase dimmable, round. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, trailing-edge phase dimmable, dimensions of converter: L 110 x W 50 x H 19 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Cast iron / Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 680lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, Control: Trailing-edge phase.

|                    |                  |
|--------------------|------------------|
| <b>Artikel-Nr.</b> | <b>39141023</b>  |
| <b>Stand:</b>      | 25.10.2021 20:35 |

|                                    |   |
|------------------------------------|---|
| Colour temperature                 | 3000 K                                  |
| Beam angle                         | 38 °                                    |
| Amount of light sources / fittings | 1 Qty                                   |
| Material                           | Cast iron / Aluminium / Glass / Plastic |
| Lamp                               | LED                                     |
| Colour rendering                   | CRI > 80                                |
| Control                            | Trailing-edge phase                     |
| Outer diameter                     | 88 mm                                   |

|                      |                     |
|----------------------|---------------------|
| Built-in diameter    | 68 mm               |
| Installation depth   | 50 mm               |
| Voltage              | 230V AC 50Hz        |
| Degree of protection | IP20                |
| Protection class     | II                  |
| Circlip              | Without circlip     |
| Adjustability        | Pivoted             |
| Swivel angle         | 25 °                |
| Circuit type         | Parallel conduction |