



Special features

- Light colour adjustable in 3 stages
- 230 V direct connection
- Including power supply

Housing Material	Aluminium
Housing Color	White
Material of Lens	Plastic
Protection Class Lamp	Protection class III/safety extra-low voltage
Protection Class Power Plug	Protection class II/protective insulation
Rated Input	30.5 W
Rated Input Voltage	220-240 V/AC
Power Supply Unit incl.	Yes
Dimmable	No
Motion Detector	No

Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	31 kWh/1000h
Energy Efficiency Class	E

Light Source	LED, Light source changeable TC
Color Temperature	3000/4000/6000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	3900/4320/4140 lm
Rated Luminous Flux 2	4320 lm
Luminous Efficiency	135.7 lm/W
Rated Angle of Reflection	120 Degree
UGR	22

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	620 mm
Width	620 mm
Height	32 mm

Working Temperature	-20 to 45 °C
Storage Temperature	-40 to 80 °C
IP Protection Class	IP 40
IK Protection Class	IK03