

## Han 1HC-Bu-S-M12, 650A



Image is for illustration purposes only. Please refer to product description.

Part number	09 11 001 2775
Specification	Han 1HC-Bu-S-M12, 650A
HARTING eCatalogue	<a href="https://b2b.harting.com/09110012775">https://b2b.harting.com/09110012775</a>

### Identification

Category	Inserts
Series	Han <sup>®</sup> HC Modular
Identification	650

### Version

Termination method	Screw termination
Gender	Female
Details	Please ensure to hold up the contact with a wrench size 24 to apply the tightening torque

### Technical characteristics

Conductor cross-section	240 mm <sup>2</sup>
Rated current	650 A
Rated voltage	4,000 V
Rated impulse voltage	18 kV
Pollution degree	3
Insulation resistance	>10 <sup>10</sup> Ω
Contact resistance	≤0.2 mΩ
Tightening torque	16 ... 18 Nm
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500
Vibration resistance	Category 1B acc. to IEC 61373



Pushing Performance  
Since 1945

## Technical characteristics

Shock resistance Category 1B acc. to IEC 61373

## Material properties

Material (insert)	Polycarbonate (PC) Polyamide (PA)
Colour (insert)	RAL 7032 (pebble grey)
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26

## Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076

## Commercial data

Packaging size	1
Net weight	479.8 g
Country of origin	Romania
European customs tariff number	85359000



**Pushing Performance**  
Since 1945

## Commercial data

GTIN	5713140016118
eCl@ss	27440205 Contact insert for industrial connectors