



The ALKES series is not a traditional wall-mounted light but reminds you of a floodlight with its SMD-LED panel. The highlight: the upper housing part is tilted forwards 45° from the façade to direct the warm white light in a targeted manner onto the surface to be illuminated. In addition, the ALKES also looks great when switched off with its modern design and rounded edges.

Special features

- High luminous efficacy
- Homogeneous light distribution
- Die-cast aluminium housing

Housing Material	Die-cast aluminium	Power Consumption	21 kWh/1000h
Housing Color	Grey	Energy Efficiency Class	G
Material of Lens	Glass		
Protection Class	Protection class I/protective grounding		
Rated Input	21 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	920 lm		
Rated Angle of Reflection	110 Degree		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	200 mm		
Width	126 mm		
Height	184 mm		
Working Temperature	-20 to 50 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 65		
Life Time L70 / B50	26500 h		
Switching Cycles	15000		