

**Special features**

- Including 2 m connecting cable with IP44 plug
- Including wireless remote control with approx. 20 m range.

Housing Material	Plastic	IP Protection Class Plug	IP 44
Housing Color	Black	Life Time L70 / B50	25000 h
Protection Class	Protection class I/protective grounding	Switching Cycles	100000
Rated Input	11 W	Power Consumption	11 kWh/1000h
Rated Input Voltage	200-240 V/AC 50 / 60 Hz		
Frequency			
Power Supply Unit incl.	Yes		
Connection Cable Primary	Yes		
Primary Connection	Power plug IP44		
Primary Cable Length	2 m		
Connection Type According to Standard	Typ Y		
Dimmable	Yes		
Control technology	RF 2,4 GHz		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Colour Consistency	6 SDCM		
Rated Luminous Flux	270 lm		
Rated Angle of Reflection	115 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top		
Length	133 mm		
Width	57 mm		
Height	179 mm		
Working Temperature	-20 to 50 °C		
Storage Temperature	-40 to 60 °C		
IP Protection Class Lamp	IP 65		