

Plug - with screwless terminals, for harsh applications



| Product description | |
|---------------------------|-----------------------|
| BALS-Prd.-Nr | 21754 |
| EAN | 4024941217545 |
| Product category | QUICK-CONNECT TE plug |
| Current | 16A |
| Number of poles | 5p |
| Arrangement of phases | 3p+N+PE |
| Position of earth contact | 7 h |
| Voltage | 277/480 - 288/500V~ |
| Frequency | 50/60Hz |

| Product description | |
|------------------------|--|
| Protection degree | IP67 |
| Colour code | black RAL 9005 |
| Colour of appliance | Collar black RAL 9005, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035, Housing cover black RAL 9005 |
| Connection design | screwless spring-clamp technology |
| Maximum conductor size | 2,5 qmm |
| Cable entry | Cable gland |
| Height | 154mm |
| Width | 74mm |
| Depth | 74mm |
| Material of enclosure | Polyamide |
| Contacts | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties | |
|---------------------------------|--|
| | For cable diameter from 10 up to max. 21 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.215 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941217545 |

| Logistics data | |
|----------------|---------------|
| Length | 74 mm |
| Width | 74 mm |
| Height | 154 mm |
| Weight | 0.216 kg |
| Volume | 843.304 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941831963 |
| Length | 258 mm |
| Width | 183 mm |
| Height | 212 mm |
| Weight | 2.302 kg |
| Volume | 8,750 ccm |

