



**Special features**

- Flicker-free
- Secured against short circuits and overloads

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	Black
<b>Operating Mode</b>	Constant voltage
<b>Protection Class</b>	Protection class II/protective insulation
<b>Power</b>	12 W
<b>Output Voltage</b>	12 V/DC
<b>Output Current</b>	0-1000 mA
<b>Power Factor</b>	0.90
<b>Connection Type</b>	Open cables
<b>Primary Connection</b>	With free strand / conductor ends
<b>Secondary Connection</b>	Open cables
<b>Number of Circuit Breaker B10A max.</b>	17
<b>Number of Circuit Breaker B16A max.</b>	27
<b>Number of Circuit Breaker C10A max.</b>	36
<b>Number of Circuit Breaker C16A max.</b>	58
<b>Inrush Current max.</b>	15 A / 200 µs
<b>Capacitive Load</b>	1017 µF
<b>Reference Point Tc</b>	85 °C
<b>Working Temperature</b>	-20 to 50 °C
<b>Storage Temperature</b>	-20 to 70 °C
<b>IP Protection Class</b>	IP 65
<b>Life Time</b>	30000 h
<b>Length</b>	50 mm
<b>Width</b>	48 mm
<b>Height</b>	24 mm
<b>Product weight</b>	77 g

