



Housing Material Aluminium
Housing Color White
Material of Lens PMMA
Halogen free Yes
Functions Leuchte kann mit Gleichstrom aus einer Zentralbatterie eines Notstromsystems betrieben werden., Korridorfunktion mit extern verbauten DALI-Sensor., Phase switch

Length 1528 mm
Width 656 mm
Height 310 mm
Product weight 2050 g
Working Temperature -25 to 50 °C
Storage Temperature -25 to 85 °C
IP Protection Class IP 40
IK Protection Class IK04

Protection Class Protection class I/protective grounding
Rated Input 70 W
Rated Power Consumption Standby 0.3 W
Rated Input Voltage 198-264 V/AC
Dimmable Yes
Control DALI 2 / DT6, Push-Dim
Voltage range DC 168-275 V/DC
Voltage range emergency lighting 186-250 V/DC
EOFI 15 %

Life Time L70 / B50 130000 h
Life Time L80 / B10 72000 h
Life Time L80 / B50 85000 h
Switching Cycles 50000
Power Consumption 70 kWh/1000h

Light Source LED, Light source changeable TC
Lightcolor Neutral white
Color Temperature 4000 K
Colour Consistency 3 SDCM
Colour Rendering Index (Ra) 80
Rated Luminous Flux 12400 lm
Luminous Efficiency 177 lm/W
Rated Angle of Reflection 30 Degree
UGR 22

Light characteristics Direct
Light direction Below

