



Product Features

Gigabit-Switch, for DIN-rail-mounting, 4 x RJ 45-ports 10/100/1000 Mbit/s, 6 x Installation-ports 10/100/1000 Mbit/s, PoE-feeding of installation port by external 48 V-power supply (DC), multicast support, VLAN tagging, light grey (similar RAL 7035)

- data rates 10/100/1000 Mbit/s
- for DIN-rail mounting (8 TE, 144 mm)
- insulation class II
- protection class IP 20
- for 10 data units
- 4 front ports (slanted outlets)
- 6 PoE/PoE+ ports for permanent installation (detachable, screw terminal block, 9-pole)
- detachable, screwless plug-in terminal up to 2,5mm²
- integrated power supply: 100 V-240V AC/50-60 Hz
- power consumption: 10 VA max.
- temperature range -40°C to +45°C
- separate voltage input for PoE /PoE+ (44 - 57 V DC, power supply depending on power requirements)
- LED's for operation
- cascadable by using random front port
- autpartitioning, MDI/MDIx
- Autonegotiation
- Autosensing
- port tunking
- port Monitoring
- multicast support
- port Mirroring
- VLAN tagging gem. IEEE 802.3q
- Wake-on-LAN

Features

General

PoweroverEthernet	Yes
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921663271

Mounting types

DIN-Rail	Yes
----------	-----

Dimensions/Weights without packaging	
Length mm	90
Width mm	143
Height mm	67
Net weight piece kg	0,327
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,494
Packaging unit Width mm	185
Packaging unit Height mm	145
Packaging unit Depth mm	95
References	
Accessories	21207000, 23510201, 23510202, 23510304
Similar article	23510503, 23510505

