



| | | | |
|---|---|--------------------------------|--------------|
| Housing Material | Copper | Height | 2 mm |
| Housing Color | White | Product weight | 200 g |
| Protection Class | Protection class III/safety extra-low voltage | Working Temperature | -15 to 50 °C |
| Operating Mode | Constant voltage | Storage Temperature | -10 to 60 °C |
| Rated Input 1m | 22.5 W | IP Protection Class | IP 20 |
| Rated Input Voltage | 24 V/DC | Life Time L70 / B50 | 60000 h |
| Power Supply Unit incl. | No | Switching Cycles | 30000 |
| Connection Cable Primary | Yes | Power Consumption | 75 kWh/1000h |
| Primary Connection | With free strand / conductor ends | Energy Efficiency Class | E |
| Primary Cable Length | 1 m | | |
| Connection Cable Secondary | Yes | | |
| Secondary Connection | Open cables | | |
| Secondary Cable Length | 1 m | | |
| Dimmable | Yes | | |
| Control technology | Dimmable via optional controller | | |
| Light Source | LED, Light source not changeable | | |
| Lightcolor | Warm white (WW) | | |
| Color Temperature | 3000 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 90 | | |
| Rated Angle of Reflection | 110 Degree | | |
| Luminous Flux 1m | 2570 lm | | |
| Luminous Efficiency 1m | 114.22 lm/W | | |
| LED/Meter | 160 | | |
| Bending Radius min. | 20 mm | | |
| Total Length to be Operated max. | 5 m | | |
| Segment Length | 50 mm | | |
| Segment LED Quantity | 8 | | |
| LED Distance | 6.25 mm | | |
| Length | 5000 mm | | |
| Width | 10 mm | | |