

We **Mersen France SB** sas
15 Rue Jacques Vaucanson 69720 Saint Bonnet de Mure France

Certify that products with the registered trade mark

Mersen or / ou FERRAZ SHAWMUT

Product type
NH Fuse Switch Disconnecter

Data sheet
MULTIBLOC® 1.ST8 , Size 1, 250A, 690VAC, Design for Bottom Fitting, 1-,2-,3-,4-pole
MULTIBLOC® 2.ST8 , Size 2, 400A, 690VAC, Design for Bottom Fitting, 3-,4-pole
MULTIBLOC® 3.ST8 , Size 3, 630A, 690VAC, Design for Bottom Fitting, 3-,4-pole
MULTIBLOC® 1.RST8 , Size 1, 250A, 690VAC, Design for bus bar installation, Triple Pole
MULTIBLOC® 2.RST8 , Size 2, 400A, 690VAC, Design for bus bar installation, Triple Pole
MULTIBLOC® 800VAC, Design for Bottom Fitting 3-pole Size 1 160A and Size 2 250A

References
Size 1 / Size 2 / Size 3 + suffixes

comply with the following Directives without any exemption:

- **RoHS directive N° 2011/65/UE**
- **RoHS directive N° 2015/863**

and declare that the materials and the processes used to manufacture the above mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls(PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Date : 22/06/2020
Name : Franck SARRUS
Position : VP R&D Europe
Signature : 

Ref 0025-ROHS