

# Han S 200 CA-c-b/r 50mm<sup>2</sup> 0,5m



Part number	33 50 686 9245 005
Specification	Han S 200 CA-c-b/r 50mm <sup>2</sup> 0,5m
HARTING eCatalogue	https://b2b.harting.com/33506869245005

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	System cabling
Series	Han <sup>®</sup> S
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	Female Angled Black
Connector 2	Female Angled Red
Type of cable	Copper cable (round)
Description of the cable	Oil resistant High fuel resistance Resistance to ozone Weathering resistant

#### Version

Cable length	0.5 m
Number of cores	1
Core structure	50 mm <sup>2</sup>
Details	Not be coupled or decoupled under electrical load. Assembly and installation must be carried out by a qualified electrician.

#### Technical characteristics

Rated current	200 A
Rated voltage	1,500 V
Rated impulse voltage	8 kV

Page 1 / 2 | Creation date 2022-11-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany

Product data sheet 33 50 686 9245 005 Han S 200 CA-c-b/r 50mm<sup>2</sup> 0,5m



#### **Technical characteristics**

Pollution degree	2
Insulation resistance	>10 <sup>8</sup> Ω
Limiting temperature	-40 +120 °C unmoved -40 +90 °C moved
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP40 mated condition IP20 unmated condition (1500 V DC; 1000 V AC)
Cable diameter	13.7 mm

#### Material properties

Material (cable)	Polyolefin copolymer
Colour (cable)	Black

## Specifications and approvals

Specifications	EN 50264-3-1
	EN 60811-403 Resistance to ozone
	EN 60811-504 High low temperature resistance
	EN 60811-404 Oil resistance
	EN 60811-404 High fuel resistance
	EN 60811-404 Acid resistance
	EN 60811-404 Alkali resistance
	DIN 51900 Low fire load
	ISO 4589-2 Limiting Oxygen Index (LOI)
	EN 50618 UV resistant
	UN/ECE-R 118 fire protection for rolling stock
	ISO 6722-1

### Commercial data

Packaging size	1
Net weight	400 g
Country of origin	Germany
European customs tariff number	85444290
GTIN	5713140262348
eCl@ss	27060307 Bus cable

Page 2 / 2 | Creation date 2022-11-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany