



Product Features

Cat.6A iso-patch cord, lockable, shielded, S/FTP, LSOH, FRNC, 1 m, grey (similar RAL 7035)

- suitable für 10-Gigabit applications (bandwith 500 MHz)
- 2 x RJ45-plugs
- S/FTP-version
- suitable for all common RJ45 data applications, respectively terminal devices
- fire behavior/Euro-class: EN13501-6:Eca
- mantle material: LSOH, FRNC
- molded bending protection
- bend radius without strain-relief > 25 mm, with strain-relief > 50 mm
- conductor: stranded copper wire, bare Ø 0,42 mm (AWG 27/7)
- according to following standards:
- DIN EN 50173-1
- ISO/IEC 11801
- suitable für PoE+ according to IEEE 802.3at

Features

| General | |
|--------------------------------------|---------------|
| Design | plug/plug |
| shielded | Yes |
| Classification | Cat.6A iso |
| PoweroverEthernet | Yes |
| Halogen Free | Yes |
| Country of manufacture | CN |
| GTIN (EAN) | 4043921662991 |
| Dimensions/Weights without packaging | |
| Cable length mm | 1.000 |
| Net weight piece kg | 0,049 |
| Certifications | |
| WEEE | Yes |
| CE | Yes |
| RoHS conform | Yes |

| Logistics Information | |
|--------------------------|--|
| Packaging | polybag |
| Packaging unit Quantity | 1 |
| Packaging unit Weight kg | 0,055 |
| Packaging unit Width mm | 310 |
| Packaging unit Height mm | 220 |
| Packaging unit Depth mm | 10 |
| References | |
| Accessories | 136104030, 136104070, 136112030, 136112070, 13900304, 39200011 |
| Similar article | 21200010, 21500010, 21500310, 21500410, 21500510, 21500610 |

