


LED converter 700 mA, 1-10 V dimmable (analog)

**Artikel-Nr. 17767010**



LED converter 700 mA, 1-10 V dimmable (analog), This converter is equipped with safety devices which protect it against over-voltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.5 mm<sup>2</sup>. . Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 700 mA, Voltage: 230V AC 50Hz , Power: 20W, Control: 1-10 V.

|                    |                  |
|--------------------|------------------|
| <b>Artikel-Nr.</b> | <b>17767010</b>  |
| <b>Stand:</b>      | 06.12.2021 15:47 |

|                              |   |
|------------------------------|---|
| version                      | ohne  |
| Power                        | 2,1-20 W  |
| Current                      | 700 mA  |
| Control                      | 1-10 V  |
| Material                     | Plastic   |
| Environment temperature (ta) | -25 °C bis +50 °C                                 |
| Measure point (tc)           | max. +80 °C                                       |
| Power                        | 2,1-20 W  |
| Dimensions                   | L 110,5 x B 52 x H 22 mm                          |
| Input voltage                | AC: 110-240 V, DC: 168-280 V                      |
| scope of delivery            | Plug&Play version with 110 mm<br>P&P output cable |

|                      |                   |
|----------------------|-------------------|
| Voltage              | 230V AC 50Hz      |
| Current              | 700 mA            |
| Circuit type         | Series conduction |
| Degree of protection | IP20              |
| Protection class     | II                |
| Voltage type         | DC                |
| Length               | 110.5 mm          |
| Width                | 52 mm             |
| Aufbauhöhe           | 22 mm             |