

EnOcean Easyclickpro temperature and humidity sensor

Product Data Sheet



Number of channels	1
Transmission range	30Metre
Halogen free	Yes
RAL-number (akin)	9010
Transparent	No
Signal transmission	Radio control
Mounting method	Other
Material	Plastic
Material quality	Thermoplastic
Surface protection	Untreated
Surface finishing	Glossy
Colour	White

EnOcean Easyclickpro temperature and humidity sensor

EnOcean Easyclickpro temperature and humidity sensor The Easyclickpro temperature and humidity sensor is wireless and completely maintenance-free with an internal solar-powered energy store. Multi-day operation in the dark is possible. The signal is transmitted cyclically every 11 to 24 minutes (randomly) or immediately in the event of changes greater than + -0.5 K or + -3% humidity. A backup battery (CR1225) can be used as an option. Technical specifications: Frequency: 868.3 MHz EnOcean profile: EEP A5-04-03 Measuring range temperature: -20 to +60 ° C, resolution 0.1 K Accuracy temperature: + -0.5K over the entire measuring range Measuring range humidity: 0 to 100% rH, resolution 0.4% rH Accuracy humidity: + -3% from 20 to 80%, otherwise + - 4.5% Measurement interval: every 100 seconds Power supply: solar-powered energy storage device for artificial light (optional CR1225 battery can be used) Minimum illuminance: min 1200lxh per day (25 ° C) Operation in darkness Protection class: IP40, only suitable for indoor use Ambient conditions: -20 to +60 ° C non-condensing Color: similar to RAL 9010 Dimensions: 76.2 x 22 x 15 mm

Material No.	Article No.	EAN-code
00367106	D 450 FU TH	4010105367102

PEHA Elektro GmbH & Co.KG

a Honeywell Company
Daimlerstraße 4
58553 HALVER
DEUTSCHLAND

Tel.: 02353 9118 001
Fax: 02353 9118 311
mail: peha@honeywell.com
www.peha.de

Änderungen vorbehalten. © Honeywell PEHA