



Special features

- Dimmable

Housing Material	Aluminium
Housing Color	Grey
Housing Surface	Matt
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	2.3 W
Rated Input Voltage	12 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	1.5 m
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Storage Temperature	-20 to 80 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	3 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	220 lm
Rated Angle of Reflection	120 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	190 mm
Width	60 mm
Height	5 mm

Working Temperature	-20 to 40 °C
----------------------------	--------------