

## Panel mounting socket outlet, straight - 7 poles, flange 75x75




| Product description       |  |
|---------------------------|--|
| BALS-Prd.-Nr              | 13329                                  |
| EAN                       | 4024941133296                          |
| Product category          | Panel mounting socket outlet, straight |
| Current                   | 32A                                    |
| Number of poles           | 7p                                     |
| Poles                     | 6p+PE                                  |
| Position of earth contact | 6 h                                    |
| Voltage                   | 400V                                   |

| Product description            |  |
|--------------------------------|--|
| Frequency                      | 50 and 60Hz  |
| Protection degree              | IP44   |
| Colour code                    | red RAL 3000   |
| Colour of appliance            | Hinged lid red RAL 3000, Enclosure grey RAL 7035                 |
| Connection design              | with screw terminal  |
| Maximum conductor size         | 10,0 qmm   |
| Cable entry                    | other  |
| Height                         | 98mm   |
| Width                          | 75mm   |
| Depth                          | 82mm   |
| Flange size vertical           | 75mm   |
| Flange size horizontal         | 75mm   |
| Drill hole distance vertical   | 60mm   |
| Drill hole distance horizontal | 60mm   |
| Material of enclosure          | Polyamide  |
| Contact                        | The contact carrier is made of polyamide, The contacts are brass |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.269 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |

| Logistics data |               |
|----------------|---------------|
| EAN            | 4024941133296 |
| Length         | 82 mm         |
| Width          | 75 mm         |
| Height         | 98 mm         |
| Weight         | 0.27 kg       |
| Volume         | 602.7 ccm     |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941968171 |
| Length         | 245 mm        |
| Width          | 177 mm        |
| Height         | 185 mm        |
| Weight         | 2.823 kg      |
| Volume         | 7,140 ccm     |



4 MB 389

| Ampere Polzahl             | 16   | 32   |  |  |  |  |  |
|----------------------------|------|------|--|--|--|--|--|
| a                          | 75,0 | 75,0 |  |  |  |  |  |
| b                          | 75,0 | 75,0 |  |  |  |  |  |
| c                          | 60,0 | 60,0 |  |  |  |  |  |
| d                          | 60,0 | 60,0 |  |  |  |  |  |
| e ø                        | 5,5  | 5,5  |  |  |  |  |  |
| f                          | 7,0  | 8,0  |  |  |  |  |  |
| h                          | 28,0 | 38,0 |  |  |  |  |  |
| i                          | 53,0 | 62,0 |  |  |  |  |  |
| k                          | 85,0 | 98,0 |  |  |  |  |  |
| l ø                        | 60,0 | 60,0 |  |  |  |  |  |
| m                          | 11,0 | 17,0 |  |  |  |  |  |
| Leiter mm <sup>2</sup> min | 1,5  | 2,5  |  |  |  |  |  |
| Leiter mm <sup>2</sup> max | 4    | 10   |  |  |  |  |  |