



Whilst flat surfaces and covers are the go-to for most surface-mounted ceiling lights, the ZANIAH places special emphasis on its 360° lamp [either a 12W, 18W or 21W variant]. This isn't just for visual reasons, as the ZANIAH can be combined with covers from the similarly new ORBIT series if needed. This means that not only are different colours available - the ZANIAH itself comes in eight colour variants per performance class.

Special features

- 360° light emission angle
- Dimmable

Housing Material	Aluminium	Switching Cycles	25000
Housing Color	White	Power Consumption	12 kWh/1000h
Material of Lens	Plastic	Energy Efficiency Class	F
Protection Class	Protection class II/protective insulation		
Rated Input	12 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	1510 lm		
Rated Angle of Reflection	120 Degree		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Below, Rear		
Height	42 mm		
Diameter	290 mm		
Working Temperature	-20 to 45 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 20		
IK Protection Class	IK05		
Life Time L70 / B50	50000 h		