



Special features

- Base L x W x H: 327 x 28 x 160 mm
- Including 2 m connecting cable with IP44 plug

Housing Material	Die-cast aluminium
Housing Color	Black
Material of Lens	Acryl
Protection Class	Protection class I/protective grounding
Rated Input	82 W
Rated Input Voltage	220-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Power plug IP44
Primary Cable Length	2 m
Connection Type According to Standard	Typ Y
Dimmable	No
Motion Detector	No

Base width	28 mm
Base height	160 mm
Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class Lamp	IP 65
IP Protection Class Plug	IP 44
Life Time L70 / B50	30000 h
Switching Cycles	50000
Power Consumption	82 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	8400 lm
Rated Angle of Reflection	75 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	180 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Length	316 mm
Width	286 mm
Height	41 mm
Base length	327 mm

