



The power supply unit series with up to 240 W and a cross-section of just 32 x 23 mm has impressive output potential under its „bonnet“! This power supply unit is therefore suitable for most ceiling covers, shadow gaps or any other installation situations where space is limited.

Special features

- Compact design
- Flicker-free
- Short-circuit-proof, overload protection, overheating protection
- Ideal for installation in ceiling covers

| | |
|--------------------------------------------|-------------------------------------------|
| Housing Material | Plastic |
| Housing Color | White |
| Operating Mode | Constant voltage |
| Protection Class | Protection class II/protective insulation |
| Power | 60 W |
| Output Voltage | 24 V/DC |
| Output Current | 0-2500 mA |
| Power Factor | 0.98 |
| Connection Type | Clamp |
| Number of Circuit Breaker B10A max. | 5 |
| Number of Circuit Breaker B16A max. | 9 |
| Number of Circuit Breaker C10A max. | 12 |
| Number of Circuit Breaker C16A max. | 19 |
| Inrush Current max. | 30 A / 300 μ s |
| Capacitive Load | 451.2 nF |
| Reference Point Tc | 90 °C |
| Working Temperature | -20 to 50 °C |
| Storage Temperature | -20 to 70 °C |
| IP Protection Class | IP 20 |
| Life Time | 30000 h |
| Length | 305 mm |
| Width | 30 mm |
| Height | 17 mm |
| Product weight | 152 g |

