



Due to their flexible control options, you can use the D PROFESSION pendant lamps both in private and in commercial applications. The Up and Down version emits its light in two directions. Whilst the LEDs directed upwards generate pleasant, indirect room lighting, the LEDs directed downwards ensure defined, powerful and UGR-compliant office and work lighting for desks and more.

Special features

- High light output
- Low glare value
- Max. suspended mounting 3,000 mm
- Dimmable

Housing Material	Aluminium	Pendulum Length max.	3000 mm
Housing Color	Black	Working Temperature	-20 to 40 °C
Material of Lens	Plastic	Storage Temperature	-30 to 60 °C
Protection Class	Protection class I/protective grounding	IP Protection Class	IP 20
Rated Input	60 W	Life Time L70 / B50	50000 h
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz	Switching Cycles	25000
Power Supply Unit incl.	Yes	Power Consumption	60 kWh/1000h
Connection Type	Clamp	Energy Efficiency Class	E
Dimmable	Yes		
Control technology	1-10 V		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	7180 lm		
Rated Angle of Reflection	110 Degree		
Rated Angle of Reflection 2	24 Degree		
UGR	19		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Length	1177.4 mm		
Width	53 mm		
Height	53 mm		
Base length	560 mm		
Base width	65 mm		
Base height	38 mm		

