

DIN 41626 male connector for 230 Åm HCS



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 20 10 230 4211 |
| Specification | DIN 41626 male connector for 230 Åm HCS |
| HARTING eCatalogue | https://b2b.harting.com/20102304211 |

Identification

| | |
|----------------------------|--------------------------------|
| Category | Contacts |
| Series | DIN 41626 |
| Type of contact | FO contact |
| Description of the contact | for SI fibre (HCS®) 200/230 µm |

Version

| | |
|-----------------------|-----------------|
| Gender | Male |
| Manufacturing process | Turned contacts |

Material properties

| | |
|--------------------------------------|--|
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | b51e5b97-eeb5-438b-8538-f1771d43c17d |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |



Pushing Performance

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 5.6 g |
| Country of origin | Germany |
| European customs tariff number | 85367000 |
| eCl@ss | 27440204 Contact for industrial connectors |