



**Special features**

- Can be dimmed using DALI2/DALI1
- Intelligent touch-dimmer function (iPush)
- Can be dimmed using 0-10 V/1-10 V
- Power supply and PWM dimmer in one device
- Short-circuit-proof, overload protection, overheating protection

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	White
<b>Operating Mode</b>	Constant voltage
<b>Protection Class</b>	Protection class II/protective insulation
<b>Power</b>	40 W
<b>Output Voltage</b>	24 V/DC
<b>Output Current</b>	0-1700 mA
<b>Dimmable</b>	Yes
<b>Control</b>	DALI 2 / DT6, 0-10 V, 1-10 V, Intelli Push-Dim
<b>Number of Channels</b>	1
<b>Power Factor</b>	0.95
<b>Connection Type</b>	Clamp
<b>Reference Point Tc</b>	90 °C
<b>Working Temperature</b>	-20 to 50 °C
<b>Storage Temperature</b>	-40 to 85 °C
<b>IP Protection Class</b>	IP 20
<b>Switching Cycles</b>	25000
<b>Life Time</b>	50000 h
<b>Length</b>	185 mm
<b>Width</b>	42.5 mm
<b>Height</b>	28.5 mm
<b>Product weight</b>	161 g

