



Loading-Plan:

1	shield
2	yellow
3	white
4	orange
5	blue

- Transmission properties in accordance with ISO/IEC 11801:2002: Class D
- Temperature range: -20°C ...+60°C
- Protection level: IP67
- Recommended breakaway torque for the screw M12x1 - 0,6Nm

7	09 47 80 00 022	AWG 22/7 outdoor PVC	7,5 m
6	09 47 80 00 013	AWG 22/7 outdoor PVC	20 m
5	09 47 80 00 011	AWG 22/7 outdoor PVC	10 m
4	09 47 80 00 006	AWG 22/7 outdoor PVC	5 m
3	09 47 80 00 005	AWG 22/7 outdoor PVC	3 m
2	09 47 80 00 003	AWG 22/7 outdoor PVC	1,5 m
1	09 47 80 00 002	AWG 22/7 outdoor PVC	1 m
cont. no.	Part-No.	Type of cable	Dim. a[m]

 All Dimensions in mm Original Size DIN A 3			Techn. Character.				Nicht tolerierte Maß/Free size tolerances					
				Dat.	Name	Maßstab/Scale 2:1	M12 cord, 1xM12 angled overmolded, D-coded, cable 4xAWG 22/7					
			Detail.	19.06.09	MR							
			Insp.	19.06.09	RA							
			Stand.									
EC00234	18.08.09	MR	HARTING Electronics GmbH & Co. KG					TB 09 47 80 00 xxx				Blatt/ page
DRS476B			D-32339 ESPELKAMP									
Mod.	Dat.	Name					Sub. Sub					