



The LED pendant lamp has transparent glass for direct and indirect light distribution that is almost see-through when switched off. When the light is switched on, the pane distributes the light almost entirely without glare.

This pendant lamp is fully office-compatible with a glare value [UGR] of under 19. Bright, efficient and with a sophisticated design, this light not only stands out in any type of office environment.

#### Special features

- Very low glare value
- Light colour adjustable in 2 stages
- Transparent luminous element
- Max. suspended mounting 1,800 mm

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Black
<b>Material of Lens</b>	PMMA
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	53 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	Yes
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer
<b>Motion Detector</b>	No

<b>Working Temperature</b>	-5 to 40 °C
<b>Storage Temperature</b>	-10 to 40 °C
<b>IP Protection Class</b>	IP 40

<b>Life Time L70 / B50</b>	50000 h
<b>Life Time L80 / B50</b>	50000 h
<b>Switching Cycles</b>	25000
<b>Power Consumption</b>	53 kWh/1000h
<b>Energy Efficiency Class</b>	E

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000/4000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	90
<b>Rated Luminous Flux</b>	6100 lm
<b>Rated Angle of Reflection</b>	360 Degree
<b>UGR</b>	19
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic 120°</b>	NDLS

<b>Light Exit Surfaces</b>	2
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Top, Below

<b>Length</b>	295 mm
<b>Width</b>	1195 mm
<b>Height</b>	12 mm
<b>Base length</b>	570 mm
<b>Base width</b>	80 mm
<b>Base height</b>	50 mm
<b>Pendulum Length max.</b>	1800 mm