

# lightnet

## Basic-A1

Surface mounted luminaire - Direct light distribution

Article code: BA1OBE-830M-D300



Illustrations may only be similar and serve as an orientation.





Basic-A1. LED. Surface mounted luminaire for wall or ceiling mounting with minimalist edge. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Switchable DxH (round). D=300mm. H=75mm. Medium-power current.

1664lm. 13W. 2,2kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

## Basic-A1

Surface mounted luminaire - Direct light distribution

Article code: BA1OBE-830M-D300



Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_

Productname	Basic-A1
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Jet Black
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Control	Switchable
Length L/Diameter D (mm)	D=300mm
Height H (mm)	H=75mm
Current/Power	Medium-Power
Luminous Flux	1664lm
Power consumption	13W
Degree of protection	IP40
Certification	Prüfzeichen: ENEC
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	2,2kg

