



Abbildung ähnlich

**Product Features**

SC-D/SC-D patch cord, OS2, yellow, 5m

- MM-fibre, G50/125 Åm, grade C3 or SM-Faser E9/125Åm, grade C1
- low insertion loss
- Push-Pull - connector locking
- pre-polished ceramic ferrule, 2,5mm
- with kink protection sleeves
- life > 1000 cycles
- 5 m

**Features**

## General

Design	plug, ceramic sleeve
Classification	OS2
Halogen Free	Yes
Country of manufacture	CN
GTIN (EAN)	4043921665213

## Dimensions/Weights without packaging

Cable length mm	5.000
Cable diameter mm	3
Cable construction	9/125µm, Grade C1
Net weight piece kg	0,083

## Certifications

RoHS conform	Yes
--------------	-----

## Logistics Information

Packaging	polybag
Packaging unit Quantity	1
Packaging unit Weight kg	0,089
Packaging unit Width mm	180
Packaging unit Height mm	210
Packaging unit Depth mm	20

## References

Accessories	228030506, 228030512, 228030524, 228030606, 228030612, 228030624, 228030706, 228030712, 228030724, 228030806, 228030812, 228030824
-------------	--

## Similar article

	228050305, 228050505, 228050605, 228050705, 228050802, 228051205, 228051605
--	---