



| | | | |
|---|---|--------------------------------|--------------|
| Housing Material | Aluminium | IP Protection Class | IP 20 |
| Housing Color | Black | Life Time L70 / B50 | 43800 h |
| Housing Surface | Matt | Switching Cycles | 50000 |
| Material of Lens | Polycarbonate - PC | Power Consumption | 28 kWh/1000h |
| Protection Class | Protection class II/protective insulation | Energy Efficiency Class | E |
| Rated Input | 28 W | | |
| Rated Input Voltage Frequency | 200-240 V/AC 50 / 60 Hz | | |
| Power Supply Unit incl. | Yes | | |
| Connection Type | Adapter | | |
| Dimmable | No | | |
| Motion Detector | No | | |
| Light Source | LED, Light source not changeable | | |
| Lightcolor | Warm white (WW) | | |
| Color Temperature | 3000 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 80 | | |
| Rated Luminous Flux | 3100 lm | | |
| Luminous Efficiency | 110.7 lm/W | | |
| Rated Angle of Reflection | 110 Degree | | |
| Distribution Characteristic 120° | DLS | | |
| Light Exit Surfaces | 1 | | |
| Light characteristics | Direct | | |
| Light direction | Below | | |
| Length | 1087 mm | | |
| Width | 62 mm | | |
| Height | 32 mm | | |
| Product weight | 745 g | | |
| Working Temperature | -25 to 45 °C | | |
| Storage Temperature | -25 to 50 °C | | |