


SCHUKO Socket USB
pure white

Product Data Sheet



Halogen free	Yes
Transparent	No
Model	Other
Mounting method	Flush mounted (plaster)
Material	Plastic
Colour	White
Type of fastening	Mounting with screw
MP3	no
radio link	no
[CC00001_2]	70Millimetre
[CC00001_3]	70Millimetre
[CC00180_2]	30Millimetre

SCHUKO Socket USB
pure white

SCHUKO socket with USB charger 3.4A, USB type A + C (QC3.0) 2-pole, 16A 250 V ~, with connection terminals according to VDE 0620, with central plate for combinations, with 2 USB ports type A and type C for supplying and charging mobile devices. Technical specifications
Nominal voltage: AC 220... 250 V ~ Mains frequency: 50/60 Hz Rated current socket: 16 A. Output current USB (total): 3.4 A USB type A operation (without USB type C): USB output voltage DC 5V, charging current max.3A (max.15W) USB type C (QC3.0) operation (without USB type A): USB output voltage DC 9V, charging current max.2A (max.18W) USB output voltage DC 12V, charging current max.1.5A (max.18W) USB type A + C (parallel operation): USB output voltage DC 12V, charging current max.3.4A (max.17W) with charge current monitoring Connection type: plug-in terminal Single wire: 1.5... 2.5 mm² Use of deep flush-mounted boxes recommended

Material No.	Article No.	EAN-code
00317981	D 11.6511.02 SI USB CA	4010105317985

PEHA Elektro GmbH & Co.KG

a Honeywell Company
Daimlerstraße 4
58553 HALVER
DEUTSCHLAND

Tel.: 02353 9118 001
Fax: 02353 9118 311
mail: peha@honeywell.com
www.peha.de

Änderungen vorbehalten. © Honeywell PEHA