



Energy-efficient HIGHBAY spotlights are excellently suited for high-bay lighting. The spotlights can be mounted at the desired tilt angle thanks to the adjustable fastening sets. With the corresponding set there is also the option to suspend them or, if required, to equip them with asymmetrical lenses.

Special features

- Including adjustable fastening set
- High impact resistance
- High luminous intensity

Housing Material	Die-cast aluminium
Housing Color	Grey
Material of Lens	Plastic
Protection Class	Protection class I/protective grounding
Rated Input	150 W
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	DALI 1 / DT6
Motion Detector	No

Life Time L70 / B50	40000 h
Switching Cycles	10000
Power Consumption	150 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	5000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	16700 lm
Rated Angle of Reflection	90 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	180 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	923 mm
Width	126 mm
Height	99 mm

Working Temperature	-20 to 50 °C
Storage Temperature	-20 to 50 °C
IP Protection Class	IP 65

