

## HARTING F+B Hybridcable, PO 10m



Image is for illustration purposes only. Please refer to product description.

Part number	09 45 600 0333
Specification	HARTING F+B Hybridcable, PO 10m
HARTING eCatalogue	<a href="https://b2b.harting.com/09456000333">https://b2b.harting.com/09456000333</a>

### Identification

Category	System cabling
Element	Bulk cables
Specification	Not assembled
Type of cable	Hybrid cable (copper/copper)

### Version

Cable length	10 m
Number of cores	13
Core structure	2x 2x AWG 22
	2x 0.75 mm <sup>2</sup>
	2x 1.5 mm <sup>2</sup>
	5G 2.5 mm <sup>2</sup>

### Technical characteristics

Transmission characteristics	Cat. 5e Class D up to 100 MHz
Data rate	10 Mbit/s
	100 Mbit/s
Limiting temperature	-40 ... +90 °C
Minimum bending radius	10x Cable diameter (repeated bending)

### Material properties

Material (cable)	Polyolefin copolymer
Colour (cable)	Black



**Pushing Performance**  
Since 1945

## Specifications and approvals

Approvals	Ecolab Topactive 200
	Ecolab Topactive 500
	Ecolab Topax 66
	Ecolab Topax 990
	Ecolab Topactive OKTO

## Commercial data

Packaging size	1
Net weight	391 g/m
Country of origin	Germany
European customs tariff number	85444995
GTIN	5713140273979
eCl@ss	27060501 Hybrid cable