BRUMBERG

MIRROR LED wall surface mounted mirror luminaire, IP44

Article no. 58312003

Light. For Generations.





Tender

LED wall surface mounted mirror luminaire, IP44, Rectangular. Ceiling cut-out Installation depth mm, Weight 11,500 kg, with rotattionssymmetrical, deep, wide distributed light intensity.Luminous flux 1.788 lm, Power 1 x 24 W, System Efficiency 74 lm/W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 90, Rated life time L70/B50 at 25 °C: 60.000 h, Housing material: Crystal plate glass / Aluminium, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP44, .With electronic driver, on/off switchable.

Article data	
Article no.	58312003
GTIN	4251433921578
Series name	MIRROR
Short description	LED wall surface mounted mirror luminaire, IP44
Material	Crystal plate glass / Aluminium
Shape	Rectangular
Width	500 mm
Hight	1000 mm
Weight	11.500 kg

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 10.05.2023 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

BRUMBERG

MIRROR LED wall surface mounted mirror luminaire, IP44

Article no. 58312003

Light. For Generations.

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Luminous flux	1,788 lm
System efficiency	74 lm/W
Colour rendering	CRI > 90
Reflector	Without
Light sharing	Symmetric

Operating technology of the luminaire	
Voltage type	AC
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP44
Dimmable	No
Control	on/off
Rulh change needible	The light source of this luminaire may only be replaced by the manufacturer or a service
Bulb change possible	technician commissioned by him or a similarly qualified person.
Rated life time L70/B50 at 25 °C	60,000 h

Mounting technology	
Mounting method	Surface mounting
Place of installation	Wall-mounted
Adjustability	Not adjustable

Packing data	
Gross weight	12 kg
Length of packaging	530 mm
Packaging width	1,030 mm
Packaging hight	60 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.